

# Kazan HDPE 293-284

High Density Polyethylene  
Kazanorgsintez Joint Stock Company

Message:  
GOST / TU: TU 2243-120-00203335-2000

General Information		
Uses	Cable Jacketing	
	Wire & Cable Applications	
Appearance	Natural Color	
Forms	Pellets	
Processing Method	Film Extrusion	
Physical	Nominal Value	Unit
Density	0.940 to 0.946	g/cm <sup>3</sup>
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.50 to 0.80	g/10 min
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	> 15.0	MPa
Tensile Strain (Break)	> 700	%
Additional Information	Nominal Value	Unit
Volatiles	< 350	mg/kg

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT