ADMER™ NF410E

Linear Low Density Polyethylene

Mitsui Chemicals Europe GmbH

Message:

ADMER® NF410E is a maleic anhydride grafted, PE-LLD-based adhesive resin designed for multilayer pipes composed of PE, PEX or PE-RT with EVOH, PA or Aluminum. It offers advanced adhesion durability and good processability.

Fatures Durable Food Contact Acceptable Good Adhesion Good Processability Good Processability Uses Adhesives Food Service Applications Non-specific Food Applications Non-specific Food Applications Piping Agency Ratings FDA Food Contact, Unspecified Rature Processing Method Extrusion Physical Noninal Value Unit Post Solon ASTM D1238 Methods Solon ASTM D1238 Methods Nominal Value Unit Test Method Durable Hardness (Shore D) 50 Good ASTM D1238 Yead 980 Mina Terrole Strength Solon ASTM D230 Yead 980 Mina Terrole Strength Solon ASTM D638 Impact Nominal Value Unit Test Method Solon Impact Nominal Value Unit Test Method Impact Nominal Value Mina Terrole Strength Strin D638 Impact Nominal Value Mina Terrole Strength Test Method	General Information			
God Ahesion God Processability Uses Adesives Food Service Applications Non-specific Food Applications Non-specific Food Applications Non-specific Food Application Non-specifi	Features	Durable		
Good Processibility Uses Adhesives Food Service Applications Non-specific Food Applications Piping Agency Ratings FA Food Contact, Unspecified Retiresconteresc		Food Contact Acceptable		
Uww Adhesives Food Service Applications Non-specific Food Applications Piping Processing Method Processing Method Processing Method Dension Method Processing Method Dension Method Non-specific Food Applications Processing Method Processing Method Dension Method Processing Method Dension Method Non-specific Food Applications Method Processing Method Non-specific Food Applications Processing Method Dension Method Processing Method Nominal Value Outmoter Hardness (Shore D) Site Method Nominal Value Nerale Yeld Nominal Value Normal Value <td></td> <td>Good Adhesion</td> <td></td> <td></td>		Good Adhesion		
ActionProof Service Applications Non-specific Food Applications PipingAgency RatingsFDA Food Contact, Unspecified RativeProcessing MethodExtrusionPhysicalNominal ValueUnitDensity0.920g/cm³Density0.920g/cm³MethodMominal ValueMotional CaluePhysicalNominal ValueJointDensity0.920g/runinMethodSatt D1505MethodNominal ValueMotional CalueDurometr Hardness (Shore D)0Test MethodMechanicalNominal ValueMorialParslie Strongth240MPaTensile Strongth500%1Break240MPaImpactNominal ValueMinitUnotched Izod Impact (Area)NoreakStron D256Nominal ValueUnitTest MethodUnotched Izod Impact (Area)NoreakStron D256Nominal ValueUnitTest MethodVicat Softening Temperature121°CNorial ValueVicatStron D357Parsle Interperature121°CNorial ValueVicatStron D3576Parsle Interperature121°CSoftening Temperature120°CQiudation Induction Time (210°C)>S5minSyntaxStron D300°C°CQiudator Interperature180 to 200°CQiudator Interperature180 to 200°CQiudator Interperature </td <td></td> <td>Good Processability</td> <td></td> <td></td>		Good Processability		
ActionProof Service Applications Non-specific Food Applications PipingAgency RatingsFDA Food Contact, Unspecified RativeProcessing MethodExtrusionPhysicalNominal ValueUnitDensity0.920g/cm³Density0.920g/cm³MethodMominal ValueMotional CaluePhysicalNominal ValueJointDensity0.920g/runinMethodSatt D1505MethodNominal ValueMotional CalueDurometr Hardness (Shore D)0Test MethodMechanicalNominal ValueMorialParslie Strongth240MPaTensile Strongth500%1Break240MPaImpactNominal ValueMinitUnotched Izod Impact (Area)NoreakStron D256Nominal ValueUnitTest MethodUnotched Izod Impact (Area)NoreakStron D256Nominal ValueUnitTest MethodVicat Softening Temperature121°CNorial ValueVicatStron D357Parsle Interperature121°CNorial ValueVicatStron D3576Parsle Interperature121°CSoftening Temperature120°CQiudation Induction Time (210°C)>S5minSyntaxStron D300°C°CQiudator Interperature180 to 200°CQiudator Interperature180 to 200°CQiudator Interperature </td <td></td> <td></td> <td></td> <td></td>				
Non-specific Food Applications PipingAgency RatingsFDA Food Context. Unspecified Applications Pitoressing MethodProcessing MethodFactureProcessing MethodNominal ValueDensity0.920Density0.920Mominal Valueg/m ²ⁿ MarchangNominal ValueMominal ValueNominal ValueDensity1.6Nominal ValueUnit Context. MethodDenoreer Hardness (Shore D)50MechanicalNominal ValueMominal ValueMarchanMechanical9.00Nominal ValueMarchanInstile Strength4.01Yield9.00Naminal ValueMarchanInstile Strength5.00YieldNominal ValueInstile StrengthNominal ValueVieldNominal ValueMominal ValueNatin DispisInstile StrengthNominal ValueVield StrengthNominal ValueVield StrengthNominal ValueVield Strength10Vield Str	Uses	Adhesives		
PipigAgroy RatingPA Go Contact, Unspecified XameProcessing MethodExtsionProcessing MethodNomina VacionProjecialNomina VacionProjecialNomina VacionProjecialNomina VacionMarting State MERPI (1970/2021)InformationMarting State MERPI (1970/		Food Service Applications		
Agency RatingsFDA Food Contact, Unspecified RatireProcessing MethodExtrusionPhysicalNominal ValueUnitTest MethodDensity0920g/cm ² ASTM D1505Meth Mass-Flow Rate (MFR) (190°C/2.16 kg)1.6g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore D)50STM D2240MechanicalNominal ValueUnitTest MethodTensile StrengthNominal ValueNotalTest MethodYeld9.80MPaSTM D638Inspace24.0MPaSTM D638Inspace9.500%aASTM D536InpactNominal ValueUnitTest MethodUnotched Izod Impact (Area)Nominal ValueNotalASTM D536InpactNominal ValueNotalSTM D536InpactNominal ValueUnitTest MethodUnotched Izod Impact (Area)Noral ValueNotalASTM D536InpactNominal ValueValueASTM D526NereakS50NitASTM D525Pack Meting Temperature10CASTM D5418Oxidation Induction Time (210°C)55NinS10 1357-6ExtursionNominal ValueUnitTest MethodCylinder Zone Temp.180 to 200°CS10 1357-6Cylinder Zone Temp.180 to 200°CS10 1357-6		Non-specific Food Applications		
Processing MethodExtrusionPhysicalNominal ValueUnitTest MethodDensity0.920g/cm³ASTM D1505Meit Mass-Flow Rate (MFR) (190°C/2.16 kg)1.6g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore D)50STM D2240MechanicalNominal ValueUnitTest MethodTensile StrengthSAGNMPaYield9.80MPaTensile Stongton (Break)24.0MPaImpactNominal ValueUnitTest MethodUnnotched Izod Impact (Area)Nominal ValueUnitTest MethodUnnotched Izod Impact (Area)Nominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D256Peak Melting Temperature121°CASTM D318Oxidation Induction Time (210°C)>55minISO 11357-6ExtrusionNominal ValueUnitStol 1357-6ExtrusionNominal ValueUnitCCjilnder Zone 1 Temp.180 to 200°CCjilnder Zone 2 Temp.180 to 200°C		Piping		
Processing Method Extrusion Physical Nominal Value Unit Test Method Density 0.920 g/cm³ ASTM D1505 Melt Mass-Flow Rate (MFR) (190°C/2.16 g/10 min ASTM D1238 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore D) 50 ASTM D2240 Mechanical Nominal Value Unit Test Method Tensile Strength Vield Nominal Value MPa Yield 9.80 MPa STM D638 Impact 24.0 MPa StM D638 Impact Nominal Value Unit Test Method Unnotched Izod Impact (Area) Nominal Value Mea StM D638 Impact Nominal Value Unit Test Method Vicat Softening Temperature 100 C ASTM D55 Peak Melting Temperature 121 °C ASTM D318 Oxidation Induction Time (210°C) >55 min ISO 11357-6 Extursion Nominal Value Unit StM D318 Oxidation Induction Time (210°C) >55<				
PhysicalNominal ValueUnitTest MethodDensity0.920g/cm³ASTM D1505Melt Mass-Flow Rate (MFR) (190°C/2.16 k)1.6g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore D)50	Agency Ratings	FDA Food Contact, Unspecified Ra	ating	
Density0.920g/cm³ASTM D150SMelt Mass-Flow Rate (MFR) (190°C/2.16 kg)1.6g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore D)50	Processing Method	Extrusion		
Nelt Mass-Flow Rate (MFR) (190°C/2.16 kg)1.6g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore D)50	Physical	Nominal Value	Unit	Test Method
kg)1.6g/10 minASTM D1238HardnessNominal ValueUnitTest MethodLorometer Hardness (Shore D)50Test MethodTest MethodMechanicalNominal ValueUnitTest MethodTensile Strength9.80MPaTest MethodYield9.80MPaTest MethodBreak24.0MPaTest MethodTensile Elongation (Break)> 500%0ASTM D638Unotched Izod Impact (Area)Nominal ValueUnitTest MethodNominal ValueUnitTest MethodStM D525Peak Mething Temperature100°CASTM D525Neider Johnsch (Streichter Streichter Streich	Density	0.920	g/cm³	ASTM D1505
HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore D)50ASTM D2240MechanicalNominal ValueUnitTest MethodTensile StrengthFest MethodMPaYield9.80MPaSTM D638Break24.0MPaSTM D638ImpactNominal ValueUnitTest MethodInnotched Izod Impact (Area)Nominal ValueUnitTest MethodUnnotched Izod Impact (Area)Nominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Mething Temperature121°CASTM D3418Oxidation Induction Time (210°C)>55minISO 11357-6ExtrusionNominal ValueUnitTest MethodQinder Zone 1 Temp.180 to 200°C:Qinder Zone 2 Temp.180 to 200°C:				
Durometer Hardness (Shore D)50ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength-ASTM D638Yield9.80MPa-Break24.0MPa-Tensile Elongation (Break)> 500% 0ASTM D638ImpactNominal ValueUnitTest MethodUnnotched Izod Impact (Area)No BreakUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D318Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitCQilnder Zone 1 Temp.180 to 200°C-Qilnder Zone 2 Temp.180 to 200°C-	kg)		-	
MechanicalNominal ValueUnitTest MethodTensile StrengthASTM D638Yield9.80MPaBreak24.0MPaTensile Elongation (Break)> 500% AMominal ValueUnitTest MethodUnnotched Izod Impact (Area)No BreakVieldNominal ValueUnitTest MethodVicat Softening Temperature100°CPeak Melting Temperature121°COxidation Induction Time (210°C)> 55minStotatonNominal ValueUnitCylinder Zone 1 Temp.180 to 200°CCylinder Zone 2 Temp.180 to 200°C		Nominal Value	Unit	Test Method
Tensile StrengthASTM D638Yield9.80MPaBreak24.0MPaTensile Elongation (Break)> 500% 0ImpactNominal ValueUnitTest MethodUnnotched Izod Impact (Area)No BreakUnitTest MethodYieldNominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitCCylinder Zone 1 Temp.180 to 200°CCStrustion180 to 200°CC	Durometer Hardness (Shore D)	50		ASTM D2240
Yield9.80MPaBreak24.0MPaTensile Elongation (Break)> 500%0ASTM D638ImpactNominal ValueUnitTest MethodUnnotched Izod Impact (Area)No BreakViiASTM D256ThermalNominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitTest MethodCylinder Zone 1 Temp.180 to 200°CSC	Mechanical	Nominal Value	Unit	Test Method
Break24.0MPaTensile Elongation (Break)> 500%ASTM D638ImpactNominal ValueUnitTest MethodUnnotched Izod Impact (Area)No BreakXIM D256ThermalNominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitTest MethodQlinder Zone 1 Temp.180 to 200°CStore 1	Tensile Strength			ASTM D638
Tensile Elongation (Break)> 500%ASTM D638ImpactNominal ValueUnitTest MethodUnnotched Izod Impact (Area)No BreakVinitASTM D256ThermalNominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minIso 11357-6ExtrusionNominal ValueUnit	Yield	9.80	MPa	
ImpactNominal ValueUnitTest MethodUnnotched Izod Impact (Area)No BreakASTM D256ThermalNominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)>55minISO 11357-6ExtrusionNominal ValueUnit	Break	24.0	MPa	
ImpartInterfact (Area)No BreakASTM D256Unnotched Izod Impact (Area)Nominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitTest MethodCylinder Zone 1 Temp.180 to 200°CStore 1Substruction Time (210°C)180 to 200°CStore 1Cylinder Zone 2 Temp.180 to 200°CStore 2Cylinder Zone 2 Temp.180 to 200 <td< td=""><td>Tensile Elongation (Break)</td><td>> 500</td><td>%</td><td>ASTM D638</td></td<>	Tensile Elongation (Break)	> 500	%	ASTM D638
ThermalNominal ValueUnitTest MethodVicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitCCylinder Zone 1 Temp.180 to 200°CCCylinder Zone 2 Temp.180 to 200°C	Impact	Nominal Value	Unit	Test Method
Vicat Softening Temperature100°CASTM D1525Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitCCylinder Zone 1 Temp.180 to 200°CCCylinder Zone 2 Temp.180 to 200°C	Unnotched Izod Impact (Area)	No Break		ASTM D256
Peak Melting Temperature121°CASTM D3418Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitCylinder Zone 1 Temp.180 to 200°CCylinder Zone 2 Temp.180 to 200°C	Thermal	Nominal Value	Unit	Test Method
Oxidation Induction Time (210°C)> 55minISO 11357-6ExtrusionNominal ValueUnitCylinder Zone 1 Temp.180 to 200°CCylinder Zone 2 Temp.180 to 200°C	Vicat Softening Temperature	100	°C	ASTM D1525
ExtrusionNominal ValueUnitCylinder Zone 1 Temp.180 to 200°CCylinder Zone 2 Temp.180 to 200°C	Peak Melting Temperature	121	°C	ASTM D3418
Cylinder Zone 1 Temp.180 to 200°CCylinder Zone 2 Temp.180 to 200°C	Oxidation Induction Time (210°C)	> 55	min	ISO 11357-6
Cylinder Zone 2 Temp. 180 to 200 °C	Extrusion	Nominal Value	Unit	
	Cylinder Zone 1 Temp.	180 to 200	°C	
Cylinder Zone 3 Temp. 200 to 230 °C	Cylinder Zone 2 Temp.	180 to 200	°C	
	Cylinder Zone 3 Temp.	200 to 230	°C	

Cylinder Zone 4 Temp.	200 to 230	°
Melt Temperature	200 to 230	℃

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

