

BB-AMIDE 5005

Polyamide

BB Resins S.r.l.

Message:

BB-AMIDE 5005 is a polyamide/epoxy adduct in solution, reactive at room temperature with solid epoxy resins to be used for formulating solvent systems.

BB-AMIDE 5005, in comparison with standard polyamide resins, has the advantage not to need of normal induction time after catalysis and not to hardener under critical temperatures and moisture.

BB-AMIDE 5005 is useful for formulating anticorrosive systems, industrial maintenance and enamel paints.

General Information			
Uses	Paint		
Appearance	Amber		
Forms	Liquid		
Physical	Nominal Value		
Gardner Color	< 10.0		
Brookfield Viscosity (25°C)	4.50 to 6.50	Pa·s	
Active Content	70	%	
Amine Value	150 to 175	mg KOH/g	
Mixing Ratio - with solid epoxy resin	70	%	
Thermoset	Nominal Value		Unit
Pot Life ¹ (25°C)	600 to 720	min	
NOTE			

1. on 200 g mass with 40% solid epoxy resin

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

