Yuyao PP TL504

Polypropylene

Yuyao Tenglong Plastics Co., Ltd.

Message:

Yuyao PP TL504 is a Polypropylene product filled with 40% calcium carbonate. It can be processed by injection molding and is available in Asia Pacific. Applications of Yuyao PP TL504 include appliances, automotive, electrical/electronic applications, furniture and housings. Characteristics include: Flame Rated Chemical Resistant Good Dimensional Stability Good Processability Heat Resistant

General Information				
Filler / Reinforcement	Calcium Carbonate,40% Filler by Weight			
Features	Electrically Insulating			
	Good Chemical Resistance			
	Good Dimensional Stability			
	Good Processability			
	Good Strength			
	High Gloss			
	High Heat Resistance			
Uses	Appliance Components			
	Automotive Applications			
	Electrical/Electronic Applications			
	Furniture			
	Housings			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.30	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (230°C/2.16	4.0	(10)		
kg)	4.0	g/10 min	ASTM D1238	
Molding Shrinkage - Flow	0.50 to 0.80	%	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	45.0	MPa	ASTM D638	
Tensile Elongation (Break)	3.0	%	ASTM D638	
Flexural Modulus	2800	MPa	ASTM D790	
Flexural Strength	100	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (Area)	5.00	kJ/m²	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	

Deflection Temperature Under Load (1.8			
MPa, Unannealed)	135	°C	ASTM D648
Flammability	Nominal Value		Test Method
Flame Rating			UL 94
1.60 mm	НВ		
3.20 mm	НВ		
Injection	Nominal Value	Unit	
Drying Temperature	90.0 to 95.0	°C	
Drying Time	2.0 to 3.0	hr	
Processing (Melt) Temp	195 to 225	°C	
Mold Temperature	45.0 to 80.0	°C	
Injection Pressure	60.0 to 90.0	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

