

# TABOREN PC 26 T 20

Polypropylene Copolymer

SILON s.ro

Message:

TABOREN PC 26 T 20 is a Polypropylene Copolymer (PP Copolymer) product filled with 20% talc. It can be processed by sheet extrusion and is available in Asia Pacific or Europe. Applications of TABOREN PC 26 T 20 include housings and sheet.

Characteristics include:

Copolymer

Flame Retardant

General Information			
Filler / Reinforcement	Talc,20% Filler by Weight		
Features	Copolymer		
	Flame Retardant		
Uses	Electrical Housing		
	Sheet		
Forms	Pellets		
Processing Method	Sheet Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.25	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1.2	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	20.0	MPa	ISO 527-2/1B/50
Flexural Modulus	2200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	6.0	kJ/m <sup>2</sup>	ISO 179/1eA
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	140	°C	ISO 306/A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT