

# KRATON® G1660 H

Styrene Ethylene Butylene Styrene Block Copolymer

Kraton Polymers LLC

## Message:

Kraton G1660 H is a linear triblock copolymer based on styrene and ethylene/butylene with a polystyrene content of 31%. It is supplied from North America in the physical form identified below.

Kraton G1660 H supplied as an undusted powder crumb

Kraton G1660 H polymer is used as a modifier of thermoplastics and bitumen. It is also suitable as an ingredient in thermoplastic elastomer (TPE) compound formulations for a variety of applications and may be used in formulating adhesives, sealants, and coatings.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Copolymer		
Uses	Adhesives		
	Coating Applications		
	Compounding		
	Plastics Modification		
	Sealants		
Forms	Crumb		
Processing Method	Coating		
	Compounding		
Physical	Nominal Value	Unit	Test Method
Polystyrene Content	29 to 33	%	Internal Method
Solution Viscosity - (Toluene) 20%wt (25°C)	0.90 to 1.5	Pa·s	Internal Method
Total Extractables	< 1.0	%	Internal Method
Volatile Matter	< 1.0	%	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT