# YUPLENE® R372Y

### Polypropylene Random Copolymer SK Global Chemical

#### Message:

Yuplene R372Y is random polypropylene that is made for injection molding. It has high impact strength and excellent transparency. Since it has excellent odor property and dimensional stability, it can be used for food packaging, packaging container, and disposable syringe and various home appliances. Yuplene R372Y complies with FDA regulation 21 CFR 177.1520 for the exposure to food.

| General Information                     |                                 |          |             |
|---|---------------------------------|----------|-------------|
| Features                                | Food Contact Acceptable         |          |             |
|   | Good Dimensional Stability      |          |             |
|   | High Impact Resistance          |          |             |
|   | Low to No Odor                  |          |             |
|   |                                 |          |             |
| Uses                                    | Appliances                      |          |             |
|   | Containers                      |          |             |
|   | Food Packaging                  |          |             |
|   | Medical/Healthcare Applications |          |             |
|   |                                 |          |             |
| Agency Ratings                          | FDA 21 CFR 177.1520             |          |             |
| Appearance                              | Clear/Transparent               |          |             |
| Processing Method                       | Injection Molding               |          |             |
| Physical                                | Nominal Value                   | Unit     | Test Method |
| Melt Mass-Flow Rate (MFR) (230°C/2.16   |                                 |          |             |
| kg)                                     | 14                              | g/10 min | ASTM D1238  |
| Hardness                                | Nominal Value                   | Unit     | Test Method |
| Rockwell Hardness (R-Scale)             | 85                              |          | ASTM D785   |
| Mechanical                              | Nominal Value                   | Unit     | Test Method |
| Tensile Strength (Yield)                | 29.4                            | МРа      | ASTM D638   |
| Tensile Elongation (Break)              | > 500                           | %        | ASTM D638   |
| Flexural Modulus                        | 1080                            | МРа      | ASTM D790   |
| Impact                                  | Nominal Value                   | Unit     | Test Method |
| Notched Izod Impact (23°C)              | 64                              | J/m      | ASTM D256   |
| Aging                                   | Nominal Value                   | Unit     | Test Method |
| Accelerated Oven Aging - in Air (150°C) | 15.0                            | day      | ASTM D3012  |
| Heat Deflection Temperature             | 94                              | °C       | ASTM D648   |
| Thermal                                 | Nominal Value                   | Unit     | Test Method |
| Vicat Softening Temperature             | 135                             | °C       | ASTM D1525  |
| Optical                                 | Nominal Value                   | Unit     | Test Method |
|   |                                 |          |             |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

