

Polene LDPE S 1018

Low Density Polyethylene
TPI Polene Public Company Limited

Message:

Polene LDPE S 1018 is a Low Density Polyethylene material. It is available in Asia Pacific or North America for injection molding.
Important attributes of Polene LDPE S 1018 are:
Good Processability
Low Shrinkage
Typical applications include:
Additive/Masterbatch
Caps/Lids/Closures
Consumer Goods
Engineering/Industrial Parts
Food Contact Applications

General Information			
Features	Good Flow		
	Good Processability		
	Low Shrinkage		
Uses	Lids		
	Masterbatch		
	Thin-walled Parts		
	Toys		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.916	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	20	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	48		DIN 53505
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	9.50	MPa	
Break	8.50	MPa	
Tensile Elongation (Break)	400	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	82.0	°C	ASTM D1525
Melting Temperature	100 to 110	°C	ASTM D1238
Injection	Nominal Value	Unit	
Processing (Melt) Temp	170 to 210	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

