

Vinnolit® E 75 SK

Polyvinyl Chloride Homopolymer

Vinnolit GmbH & Co. KG

Message:

Vinnolit E 75 SK is a fine-particle sized, paste making emulsion homopolymer, classified as a low to medium viscosity resin. Plastisols made with Vinnolit E 75 SK exhibit a slightly pseudoplastic rheology. Vinnolit E 75 SK is particularly suitable for the production of compact films and chemically blown foams. Typical application is artificial leather, especially for thermoformed surfaces in the automotive applications.

General Information			
Features	Medium-low Viscosity		
Uses	Automotive Applications Foam		
Agency Ratings	EC 1907/2006 (REACH)		
Processing Method	Plastisol		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.42	g/cm ³	ISO 60
K-Value	74.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	141.0	ml/g	ISO 1628
Emulsifier Content	Medium		
Particle Size Distribution ¹	< 2.0	%	ISO 4610
Volatile Matter	< 0.30	%	ISO 1269
Fogging ²	< 1.5	mg	DIN 75201B
NOTE			
1.	retained on 0.063 mm screen		
2.	Gravimetric		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT