

Unichem 8715L-80

Polyvinyl Chloride

Colorite Polymers

Message:

Unichem 8715L-80 is a polyvinyl chloride product. It can be processed by extrusion and is available in North America. Typical application areas are: automotive industry. The main characteristics are: good weather resistance.

General Information			
Features	Good weather resistance		
Uses	Application in Automobile Field		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.22	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	37		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	20.0	MPa	ASTM D638
Tensile Elongation (Yield)	430	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	8.27	MPa	ASTM D412
Clash-Berg Modulus (-25°C)	310	MPa	ASTM D1043
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-57.2	°C	ASTM D746
Optical	Nominal Value		Test Method
Gardner Gloss (60°)	80		ASTM D523
Additional Information			

Volatile Loss (ASTM D-1203) <1.0%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 1342475533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT