

TechnoFin PPC EPDM 4820

Ethylene Propylene Diene Terpolymer

TechnoCompound GmbH

Message:

TechnoFin PPC EPDM 4820 is an ethylene propylene diene terpolymer (EPDM) material. This product is available in Europe, and the processing method is injection molding.

The typical application field of TechnoFin PPC EPDM 4820 is: automotive industry

General Information			
Appearance	Black		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm ³	ISO 1183
Melt Volume-Flow Rate (MVR) (230°C/2.16 kg)	18.0	cm ³ /10min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1200	MPa	ISO 527-2
Additional Information			
Ash Content, ISO 3451, 625°C: <10%			
Injection	Nominal Value	Unit	
Drying Temperature	60.0 - 80.0	°C	
Drying Time	2.0 - 4.0	hr	
Processing (Melt) Temp	210 - 270	°C	
Mold Temperature	20.0 - 60.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT