

DAI-EL™ G-717

Fluoroelastomer
DAIKIN AMERICA, INC.

Message:

DAI-EL G-717 is a cure-incorporated copolymer designed for transfer and compression molding applications. G-717 offers moderate cure speeds with good elongation.

General Information			
Features	Copolymer		
	Fast curing		
	Extended tensile rate		
Uses	Washer		
	Seals		
Appearance	White		
	Pink		
Forms	Particle		
Processing Method	Compression molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.81	g/cm ³	ASTM D792
Mooney Viscosity (ML 1+10, 121°C)	37	MU	ASTM D1646
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	69		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	3.00	MPa	ASTM D412
Tensile Strength (Yield)	13.7	MPa	ASTM D412
Tensile Elongation (Break)	270	%	ASTM D412
Additional Information			

All tests performed were performed under DAIKIN test methodsFluorine Content: 66%Curing characteristic, Measuring Temperature: 170°C
Curing characteristic, Curelastomer: 3.8 min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

