

Unichem 8733

Polyvinyl Chloride

Colorite Polymers

Message:

Unichem 8733 is a Polyvinyl Chloride product. It can be processed by extrusion and is available in North America. Typical application: Hose/Tubing.
Characteristics include:
Good Flexibility
Heat Resistant

| General Information | | | |
|------------------------------|------------------------|-------------------|-------------|
| Features | Good Flexibility | | |
| | Good Thermal Stability | | |
| Uses | Garden Hose | | |
| Forms | Pellets | | |
| Processing Method | Extrusion | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.33 | g/cm ³ | ASTM D792 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A) | 88 | | ASTM D2240 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength (Yield) | 20.7 | MPa | ASTM D638 |
| Tensile Elongation (Yield) | 300 | % | ASTM D638 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Stress (100% Strain) | 13.1 | MPa | ASTM D412 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT