

EnviroPro 1020GF30

Polypropylene Copolymer

West Michigan Compounding

Message:

EnviroPro 1020GF30 is a Polypropylene Copolymer (PP Copolymer) product filled with 30% glass fiber. It can be processed by injection molding and is available in North America. Primary characteristic: copolymer.

General Information			
Filler / Reinforcement	Glass Fiber,30% Filler by Weight		
Features	Copolymer		
	General Purpose		
Uses	General Purpose		
Appearance	Black		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	14	g/10 min	ASTM D1238
Ash Content	30	%	ASTM D5630
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	64.0	MPa	ASTM D638
Flexural Modulus	4100	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	110	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT