

Geon™ Vinyl Flexible 86479 Tran

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Flexible 86479 Tran is a Flexible Polyvinyl Chloride product. It can be processed by extrusion or injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Geon™ Vinyl Flexible 86479 Tran include construction applications, film and sheet.

Characteristics include:

High Gloss

UV Stabilized

General Information			
Additive	Biocide		
	UV Stabilizer		
Features	High Gloss		
	UV Absorbing		
Uses	Construction Applications		
	Film		
	Sheet		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	84		
Shore A, 15 sec	76		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹			ASTM D638
Break	16.5	MPa	
100% Strain	7.58	MPa	
Tensile Elongation ² (Break)	390	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength ³	61.3	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-40.0	°C	ASTM D746

Injection	Nominal Value	Unit
Processing (Melt) Temp	191 to 202	°C
Extrusion	Nominal Value	Unit
Melt Temperature	179 to 188	°C
NOTE		
1.	510 mm/min	
2.	510 mm/min	
3.	Die C, 510 mm/min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

