

Pujie CM40L

Chlorinated Polyethylene

Zhanhua Pujie Chemical Technology Co.,Ltd

Message:

CM40L,Low Mooney viscosity , wide molecular weight distribution, easy for processing and formulation and good sticking force with surface of other materials.

General Information		
Features	Low viscosity	
	Wide molecular weight distribution	
	Good adhesion	
Uses	Coating application	
	Fabric coating	
Physical	Nominal Value	Unit
Apparent Density	> 0.50	g/cm ³
Mooney Viscosity (ML 1+4, 125°C)	60 - 70	MU
Chlorine Content	39.0 - 41.0	wt%
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	< 65	
Mechanical	Nominal Value	Unit
Tensile Strength	> 8.00	MPa
Tensile Elongation (Break)	> 650	%
Thermal	Nominal Value	Unit
Heat of Fusion		J/g
Impurities		pcs/50 g
Volatiles		%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT