NEMCON E PP AS

Polypropylene

Ovation Polymers Inc.

Message:

Nemcon[™] E-series products are designed for use in ESDA electronic assembly environments. Nemcon[™] E PP AS is a moisture independent anti-static polypropylene characterized by consistent moldability and recyclability.

Features Antista Recycl					
Recycl	able materials				
Good	ormability		Recyclable materials		
		Good formability			
Uses Electric	Electrical components				
Tools/	Tools/Parts Box				
Bracke	t tray				
Forms Particl	9				
Physical Nomina	Value Uni	it ·	Test Method		
Specific Gravity 0.920	g/c	cm ³	ASTM D792		
Mechanical Nomina	Value Uni	it .	Test Method		
Tensile Modulus 1 (23°C)740	MP	Pa d	ASTM D638		
Tensile Strength ² (Yield, 23°C)22.0	MP	^p a ,	ASTM D638		
Tensile Elongation ³ (Break, 23°C)170	%		ASTM D638		
Flexural Modulus ⁴ (23°C, 50.0 mm Span) 525	MP	^p a i	ASTM D790		
Flexural Strength ⁵ (23°C, 50.0 mm Span) 24.0	MP	Pa a	ASTM D790		
Impact Nomina	Value Uni	it .	Test Method		
Notched Izod Impact (23°C) 93	J/m	n ,	ASTM D256		
Electrical Nomina	Value Uni	it .	Test Method		
Surface Resistivity 1.6E+11	ohr	ms ,	ASTM D257		
Additional Information					
Surface Resistivity, ASTM D257: 1e10 to 3e11 Ohms					
NOTE					
1. 50 mm/	nin				
2. 50 mm/	nin				
3. 50 mm/	nin				
4. 1.3 mm,	min				
5. 1.3 mm,	min				

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

