

CGPC PVC SO-30X (40 phr Plasticizer B)

Flexible Polyvinyl Chloride

China General Plastics Corporation

Message:

CGPC PVC SO-30X (40 phr Plasticizer B) is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific or North America for extrusion. Primary attribute of CGPC PVC SO-30X (40 phr Plasticizer B): Plasticized.
Typical application of CGPC PVC SO-30X (40 phr Plasticizer B): Fabrics/Fibers

General Information			
Additive	Plasticizer (40%)		
Uses	Fabrics		
	General Purpose		
Appearance	Translucent		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.27	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	90		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
--	20.6	MPa	
100% Strain	13.7	MPa	
Tensile Elongation (Break)	280	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Heating Volatility	0.30	%	ASTM D1203

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT