# S-RIM™ 7240 Black

### Thermoplastic

Hapco Inc.

#### Message:

 $S-RIM^{TM}$  7240 Black is a Thermoplastic product. It can be processed by structural react. inject. molding (srim) and is available in North America. Characteristics include:

Fast Molding Cycle

**Heat Resistant** 

Low Viscosity

General Information					
Features	Fast Molding Cycle				
	High Heat Resistance				
	Low Viscosity				
Appearance	Tan				
Forms	Liquid				
Processing Method	Structural React. Inject. Molding (SRIM)				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.10	g/cm³	ASTM D4669		
Molding Shrinkage - Flow	0.40 to 0.80	%	ASTM D2566		
Weight - per cubic inch	18	g			
Gel Time <sup>1</sup> (25°C)	4.0	min	ASTM D2971		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D)	84		ASTM D2240		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Modulus	2340	MPa	ASTM D638		
Tensile Strength	42.7	MPa	ASTM D638		
Tensile Elongation (Break)	11	%	ASTM D638		
Flexural Modulus	1110	MPa	ASTM D790		
Flexural Strength	60.0	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact	12	J/m	ASTM D256		
Unnotched Izod Impact	69	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (0.45 MPa, Unannealed)	112	°С	ASTM D648		
Thermoset	Nominal Value	Unit	Test Method		
Thermoset Components					
Part A	Mix Ratio by Weight: 100, Mix Ratio by Volume: 100				
Part B	Mix Ratio by Weight: 93, Mix Ratio by Volume: 100				
Thermoset Mix Viscosity (25°C)	250 to 350	сР	ASTM D4878		

Demold Time (21°C)	90	min	Internal Method
NOTE			
1.	100 g		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

