

Sumikon® FM-MK-150

Polyphenylene Sulfide

SBHPP

Message:

SUMIKON® FM-MK-150 is Glass fiber and inorganic filler filled Polyphenylene sulfide resin molding compound with good mechanical property grade. This grade is official registered UL with V-0 (t=1.0).

General Information			
Filler / Reinforcement	Glass fiber reinforced material Inorganic filler		
RoHS Compliance	RoHS compliance		
Appearance	Black		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.00	g/cm ³	ASTM D792
Molding Shrinkage			Internal method
Flow	0.20	%	Internal method
Transverse flow	0.30	%	Internal method
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	76.0	MPa	ASTM D638
Flexural Modulus	17000	MPa	ASTM D790
Flexural Strength	146	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	42	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	> 260	°C	ASTM D648
Coefficient of Linear Thermal Expansion			TMA
MD	17	ppm	TMA
TD	23	ppm	TMA
Flammability	Nominal Value		Test Method
Flame Rating (1.0 mm)	V-0		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

