

# Moplen HP2636

Polypropylene Homopolymer

LyondellBasell Industries

## Message:

Moplen HP2636 is a very high purity Polypropylene Homopolymer with increased stiffness.

The grade has been developed for BOPP Dielectric film for capacitors and Metallisable film.

Moplen HP2636 exhibits very high purity, improved thermal stability, improved stiffness, good processability, is Metallisable and has very low ash content. It does not contain slip or antiblock additives.

For regulatory information please refer to Moplen HP2636 Product Stewardship Bulletin (PSB).

General Information			
Features	Good Processability		
	Good Thermal Stability		
	High Purity		
	High Stiffness		
	Homopolymer		
	Metallizable		
Uses	Film		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	2.5	g/10 min	ISO 1133
Ash Content	< 30	ppm	ISO 3451-1
Aluminum	< 5	ppm	
Chloride	< 10	ppm	
Titanium	< 5	ppm	
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	163	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT