# Artenius XCEL M

### Polyethylene Terephthalate Glycol Comonomer

#### Artenius

### Message:

Artenius XCEL M is a highly modified copolymer of PET (Polyethylene-Terephthalate), delivered in resin pellets. Artenius XCEL M belongs to the family of PET products commonly known as "PETG" (PET Glycol modified).

It has been specially designed for use in the manufacture of a broad field of applications, such as thermoformed blisters, mono- and multilayer films, sheets, shrinkable films by extrusion process, bottles and containers by extrusion blow moulding, tubing and profiles by continuous extrusion. The material is easy to process, allows deep thermoforming, engraving, easy sealing and printing. It provides excellent gloss, clarity and high melt strength during processing.

General Information				
Features	Copolymer			
	Excellent Printability			
	Food Contact Acceptable			
	Good Melt Strength			
	Good Processability			
	High Clarity			
	High Gloss			
Uses	Bottles			
	Containers			
	Film			
	Multilayer Film			
	Profiles			
	Sheet			
	Shrink Wrap			
	Tubing			
Agency Ratings	EU 94/62/EC			
	EU No 10/2011			
Forms	Pellets			
Processing Method	Extrusion			
	Extrusion Blow Molding			
	Film Extrusion			
	Profile Extrusion			
	Sheet Extrusion			
	Thermoforming			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.29	g/cm³		

Apparent Density	0.76	g/cm³	
Viscosity Number (Reduced Viscosity)	78.0 to 82.0	ml/g	ISO 1628
Color b	< 1.00		ASTM D6290
Color L	> 64.0		ASTM D6290
Moisture	< 0.30	%	
Weight - of 20 Chips	320.0	mg	
Extrusion	Nominal Value	Unit	
Drying Temperature	65.0	°C	
Drying Time	6.0 to 8.0	hr	
Melt Temperature	190 to 250	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

