

# Topilene® R530A

Polypropylene Homopolymer

Hyosung Corporation

## Message:

Characteristics:

Transparency

FDA

DMF 21499

USP Class VI

EP 3.1.6

Applications:

IV bottle

General Information	
Additive	High Slip
Features	High Clarity
	Homopolymer
Uses	Medical Devices
	Medical/Healthcare Applications
Agency Ratings	DMF 21499
	EP Monograph 3.1.6
	FDA Unspecified Rating
	USP Class VI

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	932	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (23°C)	78	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT