# BP Flex 8000 VP BLK

### Thermoplastic Elastomer

Buckeye Polymers, Inc.

#### Message:

Product Information: Our BP Flex 8000 VP Blk material is a general purpose partially crosslinked thermoplasic elastomer using recycled content to achieve maximum economic valueand performance.

Features:

Injection molding or extrusion applications

General Information			
Features	Crosslinkable		
	General Purpose		
	Recyclable Material		
Uses	General Purpose		
Appearance	Black		
Forms	Pellets		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.920	g/cm³	ASTM D792
Water Absorption (24 hr)	0.10	%	
Hardness	Nominal Value	Unit	Test Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

**ASTM D2240** 

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

Durometer Hardness (Shore A)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

