

MIDILENA I LDPE B21/2

Low Density Polyethylene

ROMPETROL PETROCHEMICALS S.R.L.

Message:

MIDILENA I LDPE B21/2 is a Low Density Polyethylene product. It can be processed by blown film or extrusion and is available in Europe. Applications of MIDILENA I LDPE B21/2 include film and packaging.

Characteristics include:

Clarity

Slip

General Information	
Additive	Slip
Features	High Clarity
	Slip
Uses	Film
	Thin-walled Packaging
Forms	Pellets
Processing Method	Blown Film
	Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

