

TYMAX® GT1057

Low Density Polyethylene
Westlake Chemical Corporation

Message:

Westlake GT1057 is an anhydride modified acrylate copolymer designed for blown film extrusion that contains no slip and no antiblock additives. This resin is designed to function as a coextruded tie layer in multilayer film applications. Westlake GT1057 is designed to tie polyethylene to resins that typically have poor bonding characteristics such as polyamide and EVOH.

General Information	
Features	Copolymer
Uses	Film
	Packaging
	Tie-Layer
Processing Method	Blown Film
	Coextrusion
	Film Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.917	g/cm ³	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	7.5	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	87.0	°C	ASTM D3418
Peak Melting Temperature	106	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT