

Westlake PVC 1185B

Polyvinyl Chloride
Westlake Chemical Corporation

Message:

Westlake PVC 1185 PVC resin is a low molecular weight resin with excellent clarity designed for applications such as blow molding or where high plasticizer uptake is required. The excellent heat stability, clarity, cleanliness and uniformity of this product make it well suited for a broad range of applications.

Suggested Applications

Westlake PVC 1185 PVC resin is typically used in production of bottles, highly plasticized and injection molded products.

General Information	
Additive	Heat Stabilizer Plasticizer
Features	Clean/High Purity Heat Stabilized High Clarity Low Molecular Weight Plasticized
Uses	Blow Molding Applications Bottles
Appearance	White
Forms	Powder
Processing Method	Blow Molding Injection Molding

Physical	Nominal Value	Unit	Test Method
Apparent Density	0.53	g/cm ³	ASTM D1895
K-Value	56.0		
Inherent Viscosity	0.68		ASTM D5225
Particle Size			ASTM D1921
-- 1	> 99.9	%	
-- 2	< 7.00	%	
Relative Viscosity	1.85		
ASTM Classification	GP1-16050		ASTM D1755
Volatiles	0.20	%	

NOTE	
1.	Through 40 mesh
2.	Through 200 mesh

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

