

Taitacell EPS 391MM

Expanded Polystyrene

Taita Chemical Company, Ltd.

Message:

Taitacell EPS 391MM is an Expanded Polystyrene material. It is available in Asia Pacific or North America. Primary attribute of Taitacell EPS 391MM: Fast Molding Cycle.

Typical applications include:

Packaging

Wire & Cable

General Information			
Features	Fast Molding Cycle		
Uses	Insulation		
	Packaging		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.0120 to 0.0250	g/cm ³	ASTM D792
Water Content	< 0.50	%	
Bead Size ¹	1.20 to 1.80	mm	
Chemical Resistance			
Acid	Good		
Alkali	Good		
Solvent	Poor		
Expandability	70.0 to 85.0		
Mechanical	Nominal Value	Unit	Test Method
Flexural Strength	> 0.196	MPa	ASTM D790
Compressive Strength (10% Strain)	> 0.0686	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	0.033 to 0.045	W/m/K	ASTM C177
NOTE			
1.	95% min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT