

Baynat® 755 Polyol

Polyurethane

Covestro - PUR

Message:

Baynat 755 Polyol is a polyether polyol mixture used when formulating urethane headliners. The system allows low weight, good thermal dimensional stability, and high definition of surface structure. As with any product, use of Baynat 755 Polyol in a given application must be tested (including but not limited to field testing) in advance by the user to determine suitability.

General Information		
Uses	Automotive Applications	
	Automotive Interior Parts	
Forms	Liquid	
Physical	Nominal Value	Unit
Specific Gravity	1.02	g/cm ³
Apparent Density	1.02	g/cm ³
Water Content	4.2 to 4.4	wt%
Flash Point - PMCC	122	°C
Hydroxyl Value	334 to 374	mg KOH/g

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT