

Magnobond 8002

Epoxy; Epoxide

Magnolia Plastics, Inc.

Message:

Magnobond 8002 is an Epoxy; Epoxide (Epoxy) product filled with 70% silver. It is available in North America. Typical application: Adhesives/Tapes.

Characteristics include:

Conductive

Low Viscosity

General Information			
Filler / Reinforcement	Silver,70% Filler by Weight		
Features	Electrically Conductive		
	Low Viscosity		
Uses	Adhesives		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	3.99	g/cm ³	ASTM D792
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	7.5	W/m/K	ASTM C177
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	1.0E-3	ohms·cm	ASTM D257
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity	35000	cP	ASTM D2393
Demold Time (150°C)	60 to 120	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

