

# Shandong PA6 A1F01

Polyamide 6

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA6 A1F01 is a Polyamide 6 (Nylon 6) material. It is available in Asia Pacific for pipe extrusion.

Important attributes of Shandong PA6 A1F01 are:

Flame Rated

Flame Retardant

Typical applications include:

Plumbing/Piping/Potable Water

Automotive

General Information		
Additive	Flame Retardant	
Features	Flame Retardant	
Uses	Automotive Applications	
	Corrugated Pipe	
	Piping	
Processing Method	Pipe Extrusion	
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	55.0	MPa
Tensile Strain (Break)	20	%
Flexural Modulus	1200	MPa
Flexural Stress	60.0	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	6.0	kJ/m²
Charpy Unnotched Impact Strength	50	kJ/m²
Flammability	Nominal Value	Test Method
Flame Rating	V-1	UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT