

Hifax PPU X9067HS UV

Polypropylene Copolymer
LyondellBasell Industries

Message:

Hifax PPU X9067HS UV medium high melt flow, medium flexural modulus, UV-stabilized, mineral-filled HCPP copolymer with high toughness. It is primarily used for automotive exterior trim applications.

General Information	
Filler / Reinforcement	Mineral
Additive	UV Stabilizer
Features	Copolymer
	Good Stiffness
	Medium Flow
	Ultra High Toughness
Uses	Automotive Applications
	Automotive Exterior Trim

Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	14	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	22.0	MPa	ISO 527-2/50
Tensile Strain (Yield)	4.0	%	ISO 527-2/50
Flexural Modulus - Chord (23°C)	1300	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	8.0	kJ/m ²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT