

Daploy™ SF313HMS

Polypropylene Copolymer

Borealis AG

Message:

Daploy SF313HMS is a modified polypropylene.

Daploy SF313HMS is a polypropylene copolymer with high melt strength, good heat resistance and excellent heat sealing performance

General Information			
Features	Copolymer		
	Good Heat Seal		
	Good Melt Strength		
	High Heat Resistance		
	Recyclable Material		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	13	g/10 min	ISO 1133
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	148	°C	ISO 306/A
Melting Temperature	162	°C	ISO 11357-3
Peak Crystallization Temperature	124	°C	ISO 11357-3

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT