# NuSil MED-6033

#### Silicone

#### **NuSil Technology**

#### Message:

NuSil Technology's restricted materials may be considered for use in short-term implant applications, 29 days or less, or for external applications. Low consistency elastomers (LCEs) are useful alternatives to liquid silicone rubber (LSR) and high consistency rubber (HCR) for end users who need a low viscosity elastomer which provides other unique properties.

LCEs lend themselves to applications that require a pourable, self-leveling silicone. Applications include: encapsulating a device, backfilling a void, potting an electronic component that cannot withstand exposure to high heat, or prototyping a mold.

Comments: 1.41 R.I., OPTICALLY CLEAR, POURABLE

General Information			
Features	Good Processability		
	Low Viscosity		
Uses	Electrical/Electronic Applications		
	Medical/Healthcare Applications		
Agency Ratings	USP Class VI		
Appearance	Clear/Transparent		
Processing Method	Encapsulating		
	Potting		
Optical	Nominal Value		
Refractive Index	1.410		
Thermoset	Nominal Value	Unit	
Thermoset Components			
Part A	Mix Ratio by Weight: 1.0		
Part B	Mix Ratio by Weight: 1.0		
Additional Information	Nominal Value	Unit	
Cure System	Platinum		
Uncured Properties	Nominal Value	Unit	
Density	1.03	g/cm³	
Viscosity			
1	50	Pa·s	
<sup>2</sup>	75	Pa·s	
Curing Time (150°C)	0.50	hr	
Pot Life (25°C)	> 1400	min	
Cured Properties	Nominal Value	Unit	
Shore Hardness (Shore A)	50		
Tensile Strength	5.17	MPa	
Tensile Elongation at Break	310	%	

Tear Strength	14.0	kN/m	
NOTE			
1.	Part B		
2.	Part A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

