

Hostacom ERC 204 N

Polypropylene
LyondellBasell Industries

Message:

Hostacom ERC 204 N is a 10% mineral filled, polypropylene grade for injection molding. The grade features high stiffness while containing low content of fillers. The grade has been specifically designed for interior trim applications. The low density concept contributes to the reduction of final part weight. The grade features good scratch resistance and low odor. The grade is available in coloured, pellet form.

General Information			
Filler / Reinforcement	Mineral,10% Filler by Weight		
Features	High Flow		
	High Stiffness		
	Low Density		
	Low to No Odor		
	Scratch Resistant		
Uses	Automotive Applications		
	Automotive Interior Parts		
	Automotive Interior Trim		
Appearance	Unspecified Color		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.970	g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	20	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus - Secant	1900	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength			ISO 179
0°C	4.0	kJ/m ²	
23°C	6.0	kJ/m ²	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	100	°C	ISO 75-2/B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

