

# Prime 4240

Rigid Polyvinyl Chloride

Prime PVC®

## Message:

Prime 4240 is a Rigid Polyvinyl Chloride material. It is available in North America for extrusion.

Important attributes of Prime 4240 are:

Good Processability

Heat Stabilizer

Impact Resistant

General Information			
Additive	Heat Stabilizer		
Features	Good Impact Resistance		
	Good Processability		
	Heat Stabilized		
Uses	Profiles		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.34	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	79		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2830	MPa	ASTM D638
Tensile Strength (Yield)	46.9	MPa	ASTM D638
Flexural Modulus	2830	MPa	ASTM D790
Flexural Strength (Yield)	84.1	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	1100	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	71.1	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

