THERMOLAST® K TP8LDZ (Series: UV/LD/b)

Thermoplastic Elastomer

KRAIBURG TPE

Message:

The UV/LD/b Series is your material solution for applications requiring high UV resistance. It is particularly appropriate for automotive exterior. Typical applications Cowls gaskets Roof rims Water deflectors Window encapsulations Material advantages Excellent heat resistance Excellent mechanical properties Perfect adhesion to PP Perfect surface finish Tested according PV3930 for outdoor use

General Information					
Features	Good Adhesion				
	Good UV Resistance High Heat Resistance				
Uses	Automotive Exterior Parts				
	Gaskets				
Anno-100	Plack				
Appearance	Black				
Processing Method	Extrusion				
	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Density	0.970	g/cm³	ISO 1183		
Hardness	Nominal Value	Unit	Test Method		
Shore Hardness (Shore A)	79		ISO 7619		
Elastomers	Nominal Value	Unit	Test Method		
Tensile Stress ¹ (Yield)	13.5	MPa	ISO 37		
Tensile Elongation ² (Break)	750	%	ISO 37		
Tear Strength ³	28	kN/m	ISO 34-1		
Compression Set ⁴			ISO 815		
23°C, 72 hr	31	%			
70°C, 24 hr	44	%			
100°C, 24 hr	61	%			
Extrusion	Nominal Value	Unit			
Drying Temperature	60.0 to 80.0	°C			

Drying Time	2.0 to 4.0	hr
Cylinder Zone 1 Temp.	160	°C
Cylinder Zone 2 Temp.	180	°C
Cylinder Zone 3 Temp.	200	°C
Die Temperature	200 to 230	°C
NOTE		
Note		
1.	Type S2, 200 mm/min	
1. 2.	Type S2, 200 mm/min Type S2, 200 mm/min	
1.		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

