Propylplus 705

Polypropylene

Fainplast Compounds S.r.l

Message:

Propylplus 705 is a Polypropylene product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Wire & Cable.

General Information			
Uses	Wire & Cable Applications		
Physical	Nominal Value	Unit	Test Method
Density	0.870	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	0.50	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D, 15 sec)	39		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	22.0	МРа	ISO 527-2
Tensile Strain (Break)	700	%	ISO 527-2
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity (20°C)	> 1.0E+16	ohms·cm	ASTM D257

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

