

Ad-Tech Epoxy ELB-338

Epoxy; Epoxide

Ad-Tech Plastic Systems Corp.

Message:

Ad-Tech Epoxy ELB-338 is an Epoxy; Epoxide (Epoxy) product. It can be processed by laminating and is available in North America. Applications of Ad-Tech Epoxy ELB-338 include coating applications and tools.

General Information			
Features	Thixotropic		
Uses	Laminates		
	Tooling		
Appearance	Green		
Forms	Pellets		
Processing Method	Laminating		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.89	g/cm³	ASTM D1895
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	80		ASTM D2240
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
Hardener	Mix Ratio by Volume: 1.0		
	Mix Ratio by Weight: 50		
Resin	Mix Ratio by Weight: 100		
	Mix Ratio by Volume: 1.3		
Pot Life (25°C)	40	min	
Shelf Life	52	wk	
Thermoset Mix Viscosity (25°C)	65000	cP	ASTM D2393

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

