

ALPERFORM PC LDX

Polycarbonate
ALBIS PLASTIC GmbH

Message:

ALPERFORM PC LDX is a polycarbonate (PC) product. It can be processed by extrusion and is available in North America, Europe or Asia Pacific.
Features include:
Comply with REACH standard
ROHS certification


General Information			
Agency Ratings	EC 1907/2006 (REACH)		
RoHS Compliance	RoHS compliance		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Melt Volume-Flow Rate (MVR) (300°C/1.2 kg)	6.00	cm ³ /10min	ISO 1133
Extrusion	Nominal Value	Unit	
Drying Temperature	100 - 120	°C	
Drying Time	2.0 - 3.0	hr	
Melt Temperature	240 - 300	°C	
Die Temperature	250	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT