

Globalene® 8002

Polypropylene Random Copolymer
Lee Chang Yung Chemical Industry Corp.

Message:

Globalene® 8002 is a Polypropylene Random Copolymer (PP Random Copolymer) material. It is available in Asia Pacific or North America for blow molding, pipe extrusion, or sheet extrusion.
Important attributes of Globalene® 8002 are:
Copolymer
Impact Resistant
Typical applications include:
Bottles
Plumbing/Piping/Potable Water
Sheet

General Information	
Features	Good Impact Resistance
	Random Copolymer
Uses	Bottles
	Piping
	Sheet
Forms	Pellets
Processing Method	Blow Molding
	Pipe Extrusion
	Sheet Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.896	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	0.80	g/10 min	ASTM D1238
Molding Shrinkage - Flow	1.4	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	75		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	26.5	MPa	ASTM D638
Tensile Elongation (Yield)	13	%	ASTM D638
Flexural Modulus	863	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	78	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature	77	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

