

Hostalen GM 5010 T3 S RED

High Density Polyethylene

LyondellBasell Industries

Message:

Hostalen GM 5010 T3 S red is a high density polyethylene (HDPE), red colored similar RAL 3020 with light stabilizer and high melt viscosity for identification marking stripes for electrical cable protection pipes made from Hostalen GM 5010 T3 black.

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

General Information			
Additive	UV stabilizer		
Features	Viscosity, High		
Uses	Piping system		
	Sheet		
Appearance	Red		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	0.45	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Oxidation Induction Time (210°C)	> 20	min	ISO 11357-6
Extrusion	Nominal Value	Unit	
Melt Temperature	190 - 230	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

