

Sumiliteresin® PR-G-350 I

Phenolic

SBHPP

Message:

SUMILITERESIN® PR-G-350 I is a liquid resol phenolic resin water base.

Characteristics

For Coated Abrasive : good processability, optimize oven process and good coating surface. It's improve heat resistance, strength and abrasive properties.

For fiber impregnation : good processability, compatible with fiber cloth and polyester in impregnation process. It can be diluted with organic solvent such as methanol, ethanol, Aceton etc.

General Information		
Features	Workability, good	
Uses	Impregnation uses	
Appearance	Red	
Forms	Liquid	
Physical	Nominal Value	
pH (25°C)	6.8 - 8.8	
Resin Content (135°C)	73 - 79	%
Water Tolerance (25°C)	> 50	%
Uncured Properties	Nominal Value	Unit
Density (25°C)	1.26 - 1.27	g/cm ³
Viscosity (25°C)	1.0 - 1.8	Pa·s
Gel Time (150°C)	1.0 - 1.7	min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT