SABIC® BR 4610

High Cis Polybutadiene Rubber

Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® BR 4610 is a high cis-1,4 Polybutadiene rubber stabilized with a non-staining antioxidant. SABIC® BR 4610 is manufactured by solution polymerization process using stereo-specific Nickel catalyst system to control microstructure and Molecular weight distribution and provides a highly linear polymer.

Characteristics.

SABIC® BR 4610 is a medium Mooney grade generally used in blend with other elastomers and is designed for

Excellent abrasion resistance

Excellent flex cracking resistance

Excellent resilience

Good low temperature properties

Low rolling resistance

Appearence: off white to light amber

Typical applications.

Tire tread, sidewall and carcass

Conveyor belt coverings

Shoe sole, hoses and tube covers

Mechanical and sporting goods

Please take notice of specific storage and handling conditions.

This product is not intended for and must not be used in any pharmaceutical/medical applications.

General Information					
Additive	Antioxidation				
Features	Antioxidation				
	Good cracking resistance				
	Good wear resistance				
	Low temperature resistance				
	Linear polymer structure				
	Elastic				
	Medium viscosity				
Uses	Tires				
	Conveyor accessories				
	Composite				
	Pipe				
	Mixing				
	Sporting goods				
	Footwear				
Appearance	Amber				
	White-like				
Processing Method	Composite				
Physical	Nominal Value	Unit	Test Method		

Mooney Viscosity (ML 1+4, 100°C)	46	MU	ASTM D1646
1,4-cis Content	> 96.0	wt%	Internal method
Organic Acid	0.8	wt%	ASTM D5774
Ash Content		wt%	ASTM D5667
Volatiles		wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

