

# INEOS Wire & Cable B28N230

Ethylene Butyl Acrylate Copolymer

INEOS Olefins & Polymers Europe

## Message:

B28N230 is an unstabilised copolymer of ethylene and butyl acrylate containing 15 % butyl acrylate. It is designed for compounding within wire & cable applications. It can accept high amounts of fillers and could be used as base polymer for a Flame Retardant Compound.

General Information			
Features	Copolymer		
	Flame Retardant		
Uses	Compounding		
	Wire & Cable Applications		
RoHS Compliance	Contact Manufacturer		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density <sup>1</sup>	0.924	g/cm <sup>3</sup>	ISO 1183/D
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	ISO 1133
n-Butyl Acrylate Content	15.0	wt%	Internal Method
NOTE			

1. Conditioned according to ISO 1872/1

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

