

Vinnolit® K 240

Polyvinyl Chloride
Vinnolit GmbH & Co. KG

Message:

Vinnolit K 240 is a high molecular weight free-flowing specialty product based on microsuspension PVC. It is used as an anti-blocking agent, processing aid or matting agent for thermoplastic processing.

General Information			
Features	High Molecular Weight		
Uses	Blending		
Agency Ratings	EC 1907/2006 (REACH)		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.60	g/cm ³	ISO 60
Particle Size Distribution			ISO 4610
-- 1	< 10	%	
-- 2	> 50	%	
Volatile Matter	< 0.30	%	ISO 1269
NOTE			
1.	retained on 0.250 mm screen		
2.	retained on 0.063 mm screen		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT