NANCAR® 1022

Acrylonitrile Butadiene Rubber

Nantex Industry Co., Ltd.

Message:

NANCAR® 1022 is a medium high acrylonitrile butadiene copolymer, with good oil resistance. It is a crosslinked type copolymer containing sufficient non-staining stabilizers for normal storage condition.

Suggested usages include applications in automotive door panel sheet, crash pad sheet, wire and cable insulation, extruded profiles and so on. Modifying resins (EX. PVC).

General Information			
Additive	Unspecified Stabilizer		
Features	Copolymer		
	Oil Resistant		
Uses	Automotive Applications		
	Insulation		
	Profiles		
	Sheet		
	Wire & Cable Applications		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm³	
Mooney Viscosity (ML 1+4, 100°C)	40	MU	ASTM D1646
Acrylonitrile Content - Bound	33.0	%	Internal Method
Ash Content	0.60	%	Internal Method
Gel Content	75	%	Internal Method
Stabilizer	Non-staining		
Heat Loss	0.30	%	ASTM D5688

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

