

Delta HDPE 5518

High Density Polyethylene

Delta Polymers

Message:

Delta HDPE 5518 is a High Density Polyethylene product. It is available in North America.

General Information			
Features	High Density		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.953	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	18	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	22.4	MPa	ASTM D638
Flexural Modulus	1030	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	140	J/m	ASTM D256
Flammability	Nominal Value	Unit	Test Method
Burning Rate	< 100	mm/min	ISO 3795

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

