

Shandong Nylon A4TR05

Polyamide

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong Nylon A4TR05 is a Polyamide material. It is available in Asia Pacific.

Typical applications include:

Hose/Tubing

Plumbing/Piping/Potable Water

General Information		
Uses	Hose	
	Piping	
Physical	Nominal Value	Unit
Density	1.02 to 1.05	g/cm ³
Melt Mass-Flow Rate (MFR)	2.0 to 4.0	g/10 min
Hardness	Nominal Value	Unit
Shore Hardness (Shore D)	64	
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	> 40.0	MPa
Tensile Strain (Break)	> 200	%
Flexural Modulus	300 to 400	MPa
Flexural Stress	13.0 to 17.0	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	No Break	
Charpy Unnotched Impact Strength	No Break	
Thermal	Nominal Value	Unit
Melting Temperature (DSC)	185 to 195	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT