# Lushan M-12A

#### Polyolefin

### Guangzhou Lushan New Materials Co., Ltd

### Message:

Adhesive Resin for Multi-layer Oxygen Barrier Pipe

Adhesive resin Lushan series for multi-layer oxygen barrier pipe is a modified polyolefin with functional groups. It's designed to bond to a variety of barrier materials, such as nylon and ethylene vinyl alcohol (EVOH), etc.

Adhesive resin Lushan M-20A &M-12A have goods properties as below:

High bonding strength,

A wide range of bonding,

Excellent chemical bonding with barrier materials EVOH & Nylon,

Excellent heat resistance, weather resistance, chemical resistance,

Excellent mechanical properties,

Easy processing for adhesive resin,

Hygiene and safety, non-toxic residues for adhesive resin, etc.

Application: EVOH

General Information			
Features	Bondability		
	Good Chemical Resistance		
	Good Processability		
	Good Weather Resistance		
	High Heat Resistance		
	Oxygen Barrier		
Uses	Adhesives		
	Piping		
Appearance	Clear/Transparent		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16			
kg)	2.6	g/10 min	ASTM D1238
Water Content	0.060	%	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	28.0	MPa	ASTM D638
Tensile Elongation (Break)	720	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	101	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

